Industrial / Power / Data / Security / Fibre

security Cable

Part No: MC147S-W

Description Stranded 21AWG PACW, 7Cores, PVC Insulation, Aluminium Polyester Tape Overall Screen, Stranded 24AWG TACW Drain Wire, PVC Sheath.

Applicable Standards AS/ACIF S008, BS4737-3.30

For inter-connecting wiring, suitable for use in Security/Intruded Alarm

system; Use in low voltage/low current applications such as


Suitable Applications intercommunication.

Not suitable for mains connection.

Cable Construction Drawing

Cable Construction Relative Parts









Cable Description						
Conductor	AWG	Stranding	Area(mm ²)	Diameter(mm)	Material	
	21	14/0.2	0.44	0.87	PACW	
Insulation	Cores: 7 Material: PVC Colour: White, Blue, Red, Black, Yellow, Green, Brown Nominal Thickness (mm): 0.3 Nominal OD (mm): 1.5					
Screen	Material : Al. Polyester Tape			Coverage: 100%		
Drain Wire	AWG	Stranding	Area(mm ²)	Diameter(mm)	Material	
	24	7/0.2	0.22	0.6	PACW	

With Garland, you are always well connected.



Industrial / Power / Data / Security / Fibre

PVC Grey (mm) : 0.7 6.6	
----------------------------------	--

Mechanical Properties	
Operating Temperature Range	-15 to 70℃
Max. Recommended Pulling Tension	215N
Min. Bend Radius (install)	65.5mm
Approximate Mass	7.0kg/100m

SKU	Jacket Colour	Length (Metres)	Carton/Box Size (cm)	Reels/Carton	Boxes x Reels per Pallet
MC147S100W	Grey	100	46 x 24 x 17	2	40 x 2
MC147S250W	Grey	250	36 x 36 x 19	1	45 x 1 or 36 x 1
MC147S500W	Grey	500	39 x 39 x 29.5	1	12 x 1

Madison reserves the right to make changes to the products described in this specification without prior notice



All values subject to factory tolerances