• ION

info@ionups.com.au www.ionups.com.au P: 1300 700 805

F-ATS32M Automatic Transfer Switch

32 Amp

ION's Intelligent 32 Amp Automatic Transfer Switch (ATS) has been designed with two independent power inputs to supply power to the load from a primary and alternatively secondary power source in a compact 2RU foot print. Should the primary power source fail, the secondary will automatically back up the connected equipment without any interruption. The transfer time from one line to another is seamless to the connected equipment. After switching to a secondary power source, the ATS can also switch power back to the primary input when power to the primary input is restored. The ION Intelligent 32 Amp Automatic Transfer Switch (ATS) comes with a communications slot that can have an optional network card that allows for remote in network connectivity and management through HTTP, SNMP and SSH protocol.





F-ATS32M FEATURES

- 3 year advanced replacement warranty*
- Compact 2U Rackmount design
- USB and RS-232 communications
- Optional SNMP card
- 32A maximum input current
- Powered by two separately independent power sources
- Dual power supply for redundancy
- Provides seamless power switching for IT equipment
- Preferred source selection on front panel

F-ATS32M Automatic Transfer Switch

Specifications

| | F-ATS32M |
|------------------------|---|
| Output | |
| Output Voltage | 200/208/220/230/240 |
| Output Current | 32A |
| Protection | Input Breaker (option) |
| | Electronic circuit |
| Communication | RS-232, USB, Dry contact |
| | External slot for option card (F-ATSMSNMP) |
| Transfer Time (ms) | 8~12ms (Typical) |
| Efficiency | 99% (with full linear load) |
| Display | LCD+LED |
| Input | |
| Input Voltage | 200/208/220/230/240 |
| | (+/- 5% / 10% / 15% / 20%) |
| Input Voltage Range | 150Vac300Vac |
| Input Frequency | 50 / 60Hz |
| | (+/- 5% / 10% / 15% / 20%) |
| Input Current | 32A |
| Connection | |
| Input | 30A terminal 6P |
| Output | IEC C19 x 2 |
| | IEC C13 x 16 |
| Dimensions | |
| Dimensions, W x D x H: | 440 x 275 x 88mm |
| Net Weight | 6kg |
| Environment | |
| Standards Compliance | Safety: UL 60950-1/ CAN/CSA C22.2 No. 60950-1 / IEC 60950-1 |
| | EMC: FCC Part 15 / EN62310-2 |
| Standard Warranty | 3 Year Advanced Replacement* |

^{*3} Year advanced replacement warranty F-ĀTS32M please refer to the ION website for more information.