MODEL NUMBER



SPECIFICATIONS

LIVE RESOLUTION OPTIONS

1920x1080, 1280x720, 640x360

RECORDING RESOLUTION

1920x1080, 1280x720

RECORDING COMPRESSION

H.264

IMAGE SENSOR

1/2.8" Progressive Scan CMOS

LENS

2.8 mm, F1.6

ANGLE OF VIEW

108°

ANGLE ADJUSTMENT

Pan: 0 - 355°; Tilt: 0 - 75°;

Rotation: 0 - 355°

LOW- LIGHT SENSITIVITY

0 lux with IR

IR RANGE

Up to ~95 feet (30 meters)

IMAGE ADJUSTMENTS

Flip, brightness, contrast, saturation, sharpness, exposure

ETHERNET CONNECTION

10/100Mbps RJ-45

OPERATING TEMPERATURE

-22°F – 140°F (-30°C – 60°C)

OPERATING HUMIDITY

< 95% (non-condensing) RH

POWER

12 V DC ± 10%, 5W or

PoE (802.3af), 6.5W

DIMENSIONS (DxL)

4.4" x 3.2" (11.1 x 8.2 cm)

WEIGHT

1.1 lbs. (500 g)

INGRESS PROTECTION

IP67

IMPACT PROTECTION

IK10



1080p Indoor/ Outdoor Dome Camera

The ADC-VC826 from Alarm.com is a highperformance fixed dome camera optimized for indoor and outdoor video monitoring. Its discreet, compact design and outstanding HD quality video make the camera ideal for both commercial and residential video installations. The camera features a vandal-resistant exterior casing with an IP67 rating and Power over Ethernet (PoE) capabilities.

Camera Features

- Power over Ethernet
- IR night vision
- Vandal resistant
- 1080p HD video
- IP67 rated waterproof & dust-tight

Included Accessories

- Camera
- Camera stand
- Mounting hardware
- Drill template
- Hex key (Allen wrench)
- Water resistant cap